



Field Interface Cables

CBL-STN SCC 400/300 audio cable.

Sixteen (16) individually shielded twisted pairs. All conductors 22 AWG, stranded conductors. Either a 45 degree angle or straight male DB-37 connector at the DCC or DCE end. The other end is either unterminated or terminated to male DB-37 connector that mates to a Quick Connect Board (QCB-120-1).

Ordering Information

Part Number CBL-STN-AA-BC *

AA	Cable Length
05	5 foot
10	10 foot
25	25 foot
40	40 foot
60	60 foot
75	75 foot
B	connector that plugs into DCC or DCE
L	for left angled (45°)
S	for straight
R	for right angled (45°)
C	connector that plugs into the QCB
N	none (flying leads)
S	for straight
R	for angled (45°)

*Valid BC options are LN, LR, SN, SS, RN, or RR

CBL-SWT SCC-300 switch cable.

Sixteen (16) unshielded twisted pairs. All conductors 22 AWG solid conductors. Either a 45 degree angle or straight male DB-25 connector at the DCC or DCE end. The other end is either unterminated or terminated with a male DB-37 connector to mate to a Quick Connect Board. (QCB-120-2).

Ordering Information

Part Number CBL-SWT-AA-BC*

AA	Cable Length
05	5 foot
10	10 foot
25	25 foot
40	40 foot
60	60 foot
75	75 foot
B	connector that plugs into DCC or DCE
L	for left angled
S	for straight
R	for right angled
C	flying leads (no connector) or connector that plugs into the QCB
N	none
S	for straight
R	for angled

*Valid BC options are LN, LR, SN, SS, RN or RR

CBL-MST-AA Master cable for use with DCC or DCE. Male DB-15 connector. Six (6) individually shielded twisted pairs. All conductors 22 AWG, stranded conductors.

CBL-ATN-AA Audio trunk network cable for use with DCC's to create copper conductor digital audio trunks. Two (2) twisted pairs. All conductors 24 AWG, solid conductors.

CBL-140-AA For use with discrete input/output modules. Requires one cable for each input or output connector. Twenty five (25) unshielded twisted pairs, 22 AWG, solid conductors.

CBL-150-AA For use with TBE-310. Two 10 terminal Phoenix connectors. Eight (8) shielded twisted pairs, 22 AWG, stranded conductors.

The following option applies to all cables

Options	AA	Cable Length
	05	5 foot
	10	10 foot
	25	25 foot
	40	40 foot



9564 Yellowhead Trail NW
Edmonton, AB T5G 0W4
sales@harding.ca

Tel 780.462.7100
Fax 780.450.8396
www.harding.ca



Represented by: