

ICM-431 Intercom Station

Description

The ICM-431 intercom station contains a micro-controller to provide local logical functions and is used with the DXI SAB-401 station audio board or the DXL SCC-401 station control card. It is suitable for use in high security areas and is designed for superb audio clarity in reverberant acoustic environments. The ICM-431 incorporates an integral loudspeaker/microphone, and circuitry for transmission of all station audio, power, switch closures, logic, and indicator signals over a single shielded pair cable for reduced installation costs. The ICM-431 mounts in a standard three-gang electrical box.

Features


- internal termination circuitry for line fault supervision to detect open and short circuit wiring faults
- half duplex audio channel to the intercom exchange
- internal microphone preamplifier for superior audio sensitivity
- switches are programmable for call request, program selection, or other functions
- optional status indicator LED or logic functions
- LED indicator display is programmable for various status conditions
- steel offset grille baffle plate protects the speaker from physical damage
- 11 ga heavy-duty brushed stainless steel faceplate with camfired edges
- conformal coating protects all electronic components from moisture in weather resistant version
- stainless steel hardware and baffle plate in weather resistant versions
- 2.5" mylar cone speaker
- choice of 0, 1, or 2 vandal resistant long life switches
- optional solid metal piezo-electric switches provide enhanced vandal resistance and extremely long life due to the total absence of moving parts
- mechanical switches available in standard, soft action, low temperature or mushroom button versions
- available without internal speaker for remote speaker mounting
- single shielded twisted pair 22 ga cabling for audio, switch closures, LED, and logic
- 4 terminal depluggable MTA100 series connector eliminates wire stripping during servicing and installation
- mounts on standard 3 gang electrical box
- compatible with all standard #6-32 mounting hardware allowing any type of security screw to be used



Specifications

Physical	4.5" H x 6.4" W x 1.75" D (114 x 163 x 45 mm)
Faceplate	
Heavy-duty	11 ga brushed stainless steel
Environmental	
Operating Temperature	32 to 122 °F (0 to 50 °C)
Weather resistant Intercom	-40 to 122 °F (-40 to 50 °C)
Storage Temperature	-40 to 158 °F (-40 to 70 °C)
Humidity	0 to 95 % non-condensing
Field Connections	4 pin MTA100 connector
Cabling	22 ga shielded twisted pair 2500 ft (750 m) maximum length
Switch Lifetime	
Standard	1 million operations
Piezo-electric switch	50 million operations
Speaker	2.5" (64 mm) mylar cone
Speaker Level	82 dB SPL at 1 m at 1 W
Microphone Level	10 mV at 74 dB SPL

Mechanical



Ordering Information

Part number ICM-431-ABC-DEF

- | | |
|---|---|
| <p>A faceplate options</p> <ul style="list-style-type: none"> 1 14 gauge (no longer available) 2 11 gauge 3 11 gauge - labeled "Call" 4 11 gauge - labeled "Call" & "Program" 5 11 gauge - labeled "Call" & "Door" <p>B weather resistant options</p> <ul style="list-style-type: none"> 1 standard (interior) 2 weather resistant (exterior) <p>C switch B options</p> <ul style="list-style-type: none"> 0 none 1 standard 2 cord jack* 3 piezo-electric switch 4 none with header 5 standard with header 6 mini-piezo 7 anti vandal 8 red mushroom button | <p>D switch A options</p> <ul style="list-style-type: none"> 0 none 1 standard 3 piezo-electric switch 4 none with header 5 standard with header 6 mini-piezo 7 anti vandal <p>E options</p> <ul style="list-style-type: none"> 0 none 1 LED <p>F internal speaker options</p> <ul style="list-style-type: none"> 1 mylar cone |
|---|---|

* pushbutton call cord must be ordered separately



Represented by: