



SWT-110, SWT-610 Footswitch

Description

The SWT-110 footswitch contains a SPDT form C switch. Wire connections can be made to this switch through an adjustable strain relief. The SWT-110 can be used as a push-to-talk (PTT) switch with the IMS-440, MAI-420, MAI-425, MAI-625, TMM-440, TMM-441 or TMM-640.

The SWT-610 footswitch contains electronic circuitry that converts the SPDT form C switch output to a digital signal that provides PTT operation for the IMS-640 master station. An eight foot cable is supplied with the unit to connect to the IMS-640.


Features

- constructed of cast iron for long life
- non-skid base pad
- durable black finish
- 2 holes provided for rigid mounting to floor or equipment
- wide treadle offers a large seven inch target for the operators foot
- with the SWT-610 an eight foot cord is provided for connection to IMS-640 master station



Specifications

Physical Form Factor	1.78"H x 7.00"W x 5.50"D (45mm x 178mm x 140mm)
Weight	3.25 lb (1.47 kg)



Ordering Information

For IMS-440, MAI-420, MAI-425, MAI-625, TMM-440, TMM-441, TMM-640

Part number SWT-110

For IMS-640

Part Number SWT-610



7741 Wagner Road NW
Edmonton, AB T6E 5B1
sales@harding.ca

Tel 780.462.7100
Fax 780.450.8396
www.harding.ca



Represented by: