



MicroComm



MAI-420

Master Audio Interface

Description

The MAI-420 Master Audio Interface provides audio communication circuitry and control between a DXI or DXL exchange and a remote location requiring a flush mount master station with an MAI-130 keypad/display module.

Connections are available for interfacing to a loudspeaker, microphone, telephone handset and hook switch, headset, external PTT switch, phantom powered microphone.

Features

- 1 watt 45 ohm loudspeaker interface
- electret microphone interface
- phantom powered input for amplified microphones
- telephone handset interface with PTT input
- hook switch interface to activate handset
- headset interface with jack switch to detect headset connection
- 2 LED's indicate network status
- 3 LED's indicate operating status
- can be connected or removed while the system is operating without disrupting the rest of the system
- internal fuse protects circuitry
- network pass through to panel mount master station



Specifications

Physical 9" H x 6.5" W x 1.8" D
(229 x 165 x 46 mm)


Environmental
Operating Temperature 32 to 122 °F (0 to 50 °C)
Storage Temperature -4 to 158 °F (-20 to 70 °C)
Humidity 0 to 95 % non-condensing

Power Supply +12 Vdc ±10% @ 500 mA max
+24 Vdc +10% - 40% @ 500 mA max

Field Connections
Network, Power, Audio DB-25
Keyboard/Display ribbon header
Handset with 6 position terminal block
Hook Switch MTA-100-8
Speaker/Microphone MTA-100-4
Phantom Powered Microphone MTA-100-4
Headset/Jack Switch MTA-100-8

Cabling
Audio 2 22 ga shielded twisted pairs
Network 1* 22 ga unshielded twisted pair
Power 2* 22 ga pair
* Double for redundant wiring
Handset 1 SP 2 UP provided with handset
Hook Switch 22 ga 5 conductors
Speaker 22 ga 1UTP
Microphone 22 ga 1 STP
Headset/Jack Switch 22 ga
Microphone 22 ga 1 STP
Standard FCC Part 15

Mechanical



Ordering Information

Part number MAI-420-AB

- A power supply options
 - 1 12 Volt
 - 2 24 Volt
- B configurable hook switch interface
 - 0 none
 - 1 magnetic/mechanical configurable

Accessories

- IMS-130 Keyboard/Display module (required)
- Panel mount loudspeaker and microphone assembly
- Panel mount gooseneck microphone
- Headset with boom microphone
- Telephone handset with press to talk bar, cradle, and hook switch

Document # DS-MAI-420-1.9 • Copyright © 2004 Harding Instrument Co. Ltd. • All Specifications subject to change without notice • Printed in Canada



7741 Wagner Road NW
Edmonton, AB T6E 5B1
sales@harding.ca

Tel 780.462.7100
Fax 780.450.8396
www.harding.ca



Represented by: