



MicroComm



SPM-420

Station Paging Microphone

Description

The SPM-420 Station Paging Microphone is used with the MicroComm DXI and DXL intercom systems to provide a stand alone microphone that can be used for paging. The handheld push-to-talk switch allows the operator to establish and maintain a page to a specified page zone.


Features

- high quality handheld electret microphone with push-to-talk switch
- durable microphone cord that can extend up to 6 feet
- microphone comes in a robust casing made of high impact plastic
- mounts with standard 2-gang electrical box
- field connections consist of a single pair of wires
- compatible with DXL/DXI 400 series station ports



Specifications

Physical	4.5" H x 4.5" W x 1.75" D (114 x 114 x 45 mm)
Faceplate	
Heavy-duty	11 ga brushed stainless steel
Environmental	
Operating Temperature	32 to 122 °F (0 to 50 °C)
Storage Temperature	-40 to 158 °F (-40 to 70 °C)
Humidity	0 to 95 % non-condensing
Field Connections	4 pin MTA100 connector
Cabling	22 ga shielded twisted pair 2500 ft (750 m) maximum length



Ordering Information

SPM-420



9564 Yellowhead Trail NW Tel 780.462.7100
Edmonton, AB T5G 0W4 Fax 780.450.8396
sales@harding.ca www.harding.ca



Represented by: